Product Description

□□□□	2020□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□	ETPU39
□□□□□□□□□	□□□□□□3D□□□□□□□□□□□□□□□□□ PU / PU&ETPU□□□
□□□□□□□□□	□□□□□□□200□□□□□□□□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□ □□□□□□□□□□
□□□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□□1100□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□ □□□□□□□□□□
□□□□	□□□□□□□□□□□□□□□
□□	3D□□□□□□□□□□
□□	□□□□□
□□□	□□□□□□□□□□□□□□
□□□□	□□EVA□□□HI-POLY□□□PU
□□□	PU□□□
□□□	□□□□□
□□□□	38□46□□□
□□□	6 □□
□□□	□□□□□□□s□□□/□□□/□□/□□□□□□□□□□□□□□□□
□□□□□□	□□□□□□□□□□1□□□□□□□□□□10□□□□□□□□□□□□ 58.5 x 40 x 32.5 cm
□□□□□□□□□	3200□□/ 1x20 '□□□□ 6400□□/ 1x40□□□□

Product Pictures

TIGER MASTER

OIL RESISTANT
SLIP RESISTANT

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY