Product Description

□□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□	TMC4001
□□□□□□□□□	□□□□□3D□□□□□□□□□□□ PU&air max
□□□□□□□□□	□□□□□□□□□□□□□□□□□□□200□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□ □□□□□□□□□
□□□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□1100□□□□□□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□ □□□□□□□□□
□□□	0.84 kgs / pr
□□□□□	□□□□□□□□□□□□□□□□
□□	3D□□□□□□□□□□□
□□	3D□□□□□□□□□□□
□□□	□□□□□□□□□□□□□□
□□□□□□□□	□□EVA□□□HI-POLY□□□PU
□□□	□□□□
□□□	□□□
□□□□	EUR 38-46
□□□	6 □
□□□	S□□□/□□□/□□/□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□	1□□/□□□□□□□□10□□/□□□□□□□□□□□□□□58.5 x 40 x 32.5 cm
□□□□□□□□□	3300□□/ 1x20 '□□□□ 6600□□/ 1x40 ’□□□□

Product Pictures

NEW
0.42kg/pc

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N



Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY