

□□□□	□□□□□□□□□□PU□□□□□□□□□□□□
□□□□□	KS001
□□□□□□□□	□□□□□□□□PU□□□□□□□□□□
□□□□	1.□□□□□□□□□□□□□□□□□□□□2□ □ASTM F2413-05 M I / 75 C / 75□CE ENISO 20345 STANDARD□ □□□□□□□ □□□□□□□□
	2.□□□□□□□□□□□□□□
□□ □ □□□□□□□□□□□□	1□□□□□□□□□□□□□□□□□□□□□□ □ASTM F2413-05 M I / 75 C / 75□CE ENISO 20345 STANDARD□□□□□□□□□□□□□□□□□□□□□□
	2.□□□□□□□□□□
□□	□□□□
□□	□□□□
□□□	□□□□AIR □□□□□□□□□□□□
□□□□□□□□	□□□□HI-POLY
□□□	PU□□
□□□	□□ □□
□□□□	4-12□38-46□
□□□	6 □□□□□□□□□□□□□□□□
□□□□□□	□□□□□□□□□□□□□□□□□□□□□□10□□
□□□□□□□□	58.5x40x32.5cm
□□□□□□□□□□	3500□□/ 1x20 '□□□□□ 7000□□/ 1x40 '□□□□□

□□□□□□□□□□□□



