Product Description

□□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□	SJ0222
□□□□□□□□□□	□□□□□□TPU□□□□PU□□□□ PU / PU□□□□□□
□□□□□□□□□□	□□□□□□□□□□□□□□□□□□□□200□□□□□□□□□□□□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□ □□□□□□□□□□□□□□□
□□□□□□□□	□□□□□1100□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□ □□□□□□□□□□□□□□□
□□□□□□	D□□□
□□□□	□□□□□□□□
□□	PU□□□□
□□	PU□□□□
□□□	□□□□□□□□□□□□□□□□
□□□□	□□EVA□□□HI-POLY□□□PU
□□□	PU□□□
□□□	□□□□□□□
□□□□	37□47□□□
□□□	6 □□
□□□	s□□□/□□□/□□/□□□□□□□□□□□□□□□□□□□□□□
□□□□□□	□□□□□□□□□□□1□□□□□□□□□□□10□□□□□□□□□□□□ 59 x 44 x 33 cm
□□□□□□□□□□	3300□□/ 1x20 '□□□□ 6600□□/ 1x40□□□□

Product Pictures

TIGER MASTER

ABSORBER

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY