

Product Description

CE	CE
SMR02H	SMR02H
PU / PU	PU / PU
200	200 ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345
1100	1100 ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345
CE	CE
PU	PU
PU	PU
EVA HI-POLY PU	EVA HI-POLY PU
PU	PU
EUR 37-47	EUR 37-47
6	6
10	10 58.5 x 40 x 32.5 cm
3200 / 1x20 ' / 6400 / 1x40 '	3200 / 1x20 ' / 6400 / 1x40 '

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY