

## Product Description

|                 |  |
|-----------------|--|
| CE              | CE   |
| SMR11H          | SMR11H   |
| PU / PU         | PU / PU  |
| 200             | 200<br>ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345<br>1100 |
| 1100            | 1100<br>ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345        |
| CE              | CE   |
| EVA             | EVA  |
| HI-POLY         | HI-POLY  |
| PU              | PU   |
| 38              | 38   |
| 46              | 46   |
| 6               | 6  |
| 59 x 44 x 33 cm | 59 x 44 x 33 cm  |
| 3200 / 1x20     | 3200 / 1x20<br>6400 / 1x40                                   |

## Product Pictures





# Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

# SAFETY SHOES TEST



**Toecap Test  $\geq 200$  Joules**



**Midsole Test  $\geq 1200$  Newtons**



**ESD Anti-Static Test**



**Tear Strength  $\geq 120$ N**



**Bondness Test  $\geq 4.0$ N/mm**



**Flex Tester  $\geq 36,000$ T**

# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY