

Product Description

| | |
|------------|---|
| Model | SP026 |
| Material | 3D PU / PU |
| Thickness | 200 μm ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 |
| Weight | 1100 g ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 |
| | |
| Color | |
| Size | 3D |
| Material | |
| Material | EVA HI-POLY PU |
| Material | PU |
| Material | |
| Size | 38-46 |
| Material | 6 |
| Material | s/ / / |
| Dimensions | 10 58.5 x 40 x 32.5 cm |
| Weight | 3200g / 1x20 ' / 6400g / 1x40 |

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY