Product Description

[illegible]	PU[illegible]
[illegible]	SP030
[illegible]	[illegible]3D[illegible] PU / PU[illegible]
[illegible]	[illegible]200[illegible] [illegible]ASTM F2413-18 M I / 75 C / 75[illegible]CE EN ISO 20345[illegible] [illegible]
[illegible]	[illegible]1100[illegible] [illegible]ASTM F2413-18 M I / 75 C / 75[illegible]CE EN ISO 20345[illegible] [illegible]
[illegible]	[illegible]
[illegible]	3D[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]EVA[illegible]
[illegible]	PU[illegible]
[illegible]	[illegible]
[illegible]	EUR 38-46
[illegible]	6 [illegible]
[illegible]	S[illegible]/[illegible]/[illegible]/[illegible]
[illegible]	1[illegible]/[illegible]10[illegible]/[illegible]58.5 x 40 x 32.5 cm
[illegible]	3300[illegible]/ 1x20 '[illegible] 6600[illegible]/ 1x40 ’[illegible]

Product Pictures

OIL RESISTANT
SHOCK
ABSORBER

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N



Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY