

Product Description

CE	CE EN ISO 20345S1-PSRC
Model	SU024
Upper	3D PU
Weight	1.1kg
	2.0
Upper	1.1100
	2.0
Upper	3D
Upper	
Upper	
Upper	EVA
Upper	
Upper	
Upper	37-47
Upper	CE EN ISO 20345S1-PSRC
Upper	6
Upper	
Upper	1 10 58.5 X 40 X 32.5 CM
Upper	3300/1x20" 6600/1x40"

Product Pictures



200 JOULE
TOECAP



SLIP-
RESISTANT



SHOCK
ABSORPTION



ANTI-STATIC



PETROL AND
CHEMICAL
RESISTANT



ANTI-NAIL
MIDSOLE



OIL
RESISTANT



[PRODUCTION PROCESS]



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

2020 INTERSEC

SAFETY SHOES & RAIN BOOTS PROFESSIONAL



8-D32