





Company Information





EC Type Examination Certificate

	Issued to: FUJIAN HONGJIAN SHISEI CO., LTD. SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NANJI DISTRICT, SHANGHAI PROVINCE, CHINA																																																																																																																																						
	Authorised Representative: HANDEHU SHANGHAI SECURITY PRODUCTS MFG. CO., LTD. 1201 Village, Xuyuan Town, Jiangyin District, Suzhou Jiangsu Province, China																																																																																																																																						
Date of Issue: 11 January 2018	Expiry Date: 11 February 2020																																																																																																																																						
Equipment Model: LED <small>The model number and other identification information shall be clearly marked on the product and its packaging. The model number shall be clearly marked on the product and its packaging. The model number shall be clearly marked on the product and its packaging.</small>	Certificate No.: L20170002947 (extension of certificate L201702947199)																																																																																																																																						
Product Reference(s): <table border="0"> <tr><td>Light Source</td><td>LED</td></tr> <tr><td>Power</td><td>3W</td></tr> <tr><td>Beam Angle</td><td>60°</td></tr> <tr><td>Color Temperature</td><td>5000K</td></tr> <tr><td>Material</td><td>PC</td></tr> <tr><td>Mount</td><td>Recessed</td></tr> <tr><td>Input Voltage</td><td>AC 220V</td></tr> <tr><td>Output Voltage</td><td>DC 3V</td></tr> <tr><td>Output Current</td><td>100mA</td></tr> <tr><td>Output Power</td><td>0.3W</td></tr> <tr><td>Efficiency</td><td>10%</td></tr> <tr><td>Life Expectancy</td><td>50,000 hours</td></tr> <tr><td>Operating Temperature</td><td>-20°C to 40°C</td></tr> <tr><td>Storage Temperature</td><td>-30°C to 60°C</td></tr> <tr><td>Humidity</td><td>5% to 95% RH</td></tr> <tr><td>Shock</td><td>10g</td></tr> <tr><td>Vibration</td><td>10g</td></tr> <tr><td>EMC</td><td>CE</td></tr> <tr><td>RoHS</td><td>CE</td></tr> <tr><td>REACH</td><td>CE</td></tr> <tr><td>WEEE</td><td>CE</td></tr> <tr><td>Energy Label</td><td>CE</td></tr> <tr><td>Energy Efficiency Class</td><td>A</td></tr> <tr><td>Energy Consumption</td><td>0.3W</td></tr> <tr><td>Energy Consumption per Hour</td><td>0.3Wh</td></tr> <tr><td>Energy Consumption per Day</td><td>7.2Wh</td></tr> <tr><td>Energy Consumption per Month</td><td>216Wh</td></tr> <tr><td>Energy Consumption per Year</td><td>2592Wh</td></tr> <tr><td>Energy Consumption per 1000 Hours</td><td>2592Wh</td></tr> <tr><td>Energy Consumption per 10000 Hours</td><td>25920Wh</td></tr> <tr><td>Energy Consumption per 100000 Hours</td><td>259200Wh</td></tr> <tr><td>Energy Consumption per 1000000 Hours</td><td>2592000Wh</td></tr> </table>	Light Source	LED	Power	3W	Beam Angle	60°	Color Temperature	5000K	Material	PC	Mount	Recessed	Input Voltage	AC 220V	Output Voltage	DC 3V	Output Current	100mA	Output Power	0.3W	Efficiency	10%	Life Expectancy	50,000 hours	Operating Temperature	-20°C to 40°C	Storage Temperature	-30°C to 60°C	Humidity	5% to 95% RH	Shock	10g	Vibration	10g	EMC	CE	RoHS	CE	REACH	CE	WEEE	CE	Energy Label	CE	Energy Efficiency Class	A	Energy Consumption	0.3W	Energy Consumption per Hour	0.3Wh	Energy Consumption per Day	7.2Wh	Energy Consumption per Month	216Wh	Energy Consumption per Year	2592Wh	Energy Consumption per 1000 Hours	2592Wh	Energy Consumption per 10000 Hours	25920Wh	Energy Consumption per 100000 Hours	259200Wh	Energy Consumption per 1000000 Hours	2592000Wh	Description: <table border="0"> <tr><td>Construction</td><td>Recessed</td></tr> <tr><td>Mounting</td><td>Recessed</td></tr> <tr><td>Material</td><td>PC</td></tr> <tr><td>Color</td><td>White</td></tr> <tr><td>Power</td><td>3W</td></tr> <tr><td>Beam Angle</td><td>60°</td></tr> <tr><td>Color Temperature</td><td>5000K</td></tr> <tr><td>Material</td><td>PC</td></tr> <tr><td>Mount</td><td>Recessed</td></tr> <tr><td>Input Voltage</td><td>AC 220V</td></tr> <tr><td>Output Voltage</td><td>DC 3V</td></tr> <tr><td>Output Current</td><td>100mA</td></tr> <tr><td>Output Power</td><td>0.3W</td></tr> <tr><td>Efficiency</td><td>10%</td></tr> <tr><td>Life Expectancy</td><td>50,000 hours</td></tr> <tr><td>Operating Temperature</td><td>-20°C to 40°C</td></tr> <tr><td>Storage Temperature</td><td>-30°C to 60°C</td></tr> <tr><td>Humidity</td><td>5% to 95% RH</td></tr> <tr><td>Shock</td><td>10g</td></tr> <tr><td>Vibration</td><td>10g</td></tr> <tr><td>EMC</td><td>CE</td></tr> <tr><td>RoHS</td><td>CE</td></tr> <tr><td>REACH</td><td>CE</td></tr> <tr><td>WEEE</td><td>CE</td></tr> <tr><td>Energy Label</td><td>CE</td></tr> <tr><td>Energy Efficiency Class</td><td>A</td></tr> <tr><td>Energy Consumption</td><td>0.3W</td></tr> <tr><td>Energy Consumption per Hour</td><td>0.3Wh</td></tr> <tr><td>Energy Consumption per Day</td><td>7.2Wh</td></tr> <tr><td>Energy Consumption per Month</td><td>216Wh</td></tr> <tr><td>Energy Consumption per Year</td><td>2592Wh</td></tr> <tr><td>Energy Consumption per 1000 Hours</td><td>2592Wh</td></tr> <tr><td>Energy Consumption per 10000 Hours</td><td>25920Wh</td></tr> <tr><td>Energy Consumption per 100000 Hours</td><td>259200Wh</td></tr> <tr><td>Energy Consumption per 1000000 Hours</td><td>2592000Wh</td></tr> </table>	Construction	Recessed	Mounting	Recessed	Material	PC	Color	White	Power	3W	Beam Angle	60°	Color Temperature	5000K	Material	PC	Mount	Recessed	Input Voltage	AC 220V	Output Voltage	DC 3V	Output Current	100mA	Output Power	0.3W	Efficiency	10%	Life Expectancy	50,000 hours	Operating Temperature	-20°C to 40°C	Storage Temperature	-30°C to 60°C	Humidity	5% to 95% RH	Shock	10g	Vibration	10g	EMC	CE	RoHS	CE	REACH	CE	WEEE	CE	Energy Label	CE	Energy Efficiency Class	A	Energy Consumption	0.3W	Energy Consumption per Hour	0.3Wh	Energy Consumption per Day	7.2Wh	Energy Consumption per Month	216Wh	Energy Consumption per Year	2592Wh	Energy Consumption per 1000 Hours	2592Wh	Energy Consumption per 10000 Hours	25920Wh	Energy Consumption per 100000 Hours	259200Wh	Energy Consumption per 1000000 Hours	2592000Wh
Light Source	LED																																																																																																																																						
Power	3W																																																																																																																																						
Beam Angle	60°																																																																																																																																						
Color Temperature	5000K																																																																																																																																						
Material	PC																																																																																																																																						
Mount	Recessed																																																																																																																																						
Input Voltage	AC 220V																																																																																																																																						
Output Voltage	DC 3V																																																																																																																																						
Output Current	100mA																																																																																																																																						
Output Power	0.3W																																																																																																																																						
Efficiency	10%																																																																																																																																						
Life Expectancy	50,000 hours																																																																																																																																						
Operating Temperature	-20°C to 40°C																																																																																																																																						
Storage Temperature	-30°C to 60°C																																																																																																																																						
Humidity	5% to 95% RH																																																																																																																																						
Shock	10g																																																																																																																																						
Vibration	10g																																																																																																																																						
EMC	CE																																																																																																																																						
RoHS	CE																																																																																																																																						
REACH	CE																																																																																																																																						
WEEE	CE																																																																																																																																						
Energy Label	CE																																																																																																																																						
Energy Efficiency Class	A																																																																																																																																						
Energy Consumption	0.3W																																																																																																																																						
Energy Consumption per Hour	0.3Wh																																																																																																																																						
Energy Consumption per Day	7.2Wh																																																																																																																																						
Energy Consumption per Month	216Wh																																																																																																																																						
Energy Consumption per Year	2592Wh																																																																																																																																						
Energy Consumption per 1000 Hours	2592Wh																																																																																																																																						
Energy Consumption per 10000 Hours	25920Wh																																																																																																																																						
Energy Consumption per 100000 Hours	259200Wh																																																																																																																																						
Energy Consumption per 1000000 Hours	2592000Wh																																																																																																																																						
Construction	Recessed																																																																																																																																						
Mounting	Recessed																																																																																																																																						
Material	PC																																																																																																																																						
Color	White																																																																																																																																						
Power	3W																																																																																																																																						
Beam Angle	60°																																																																																																																																						
Color Temperature	5000K																																																																																																																																						
Material	PC																																																																																																																																						
Mount	Recessed																																																																																																																																						
Input Voltage	AC 220V																																																																																																																																						
Output Voltage	DC 3V																																																																																																																																						
Output Current	100mA																																																																																																																																						
Output Power	0.3W																																																																																																																																						
Efficiency	10%																																																																																																																																						
Life Expectancy	50,000 hours																																																																																																																																						
Operating Temperature	-20°C to 40°C																																																																																																																																						
Storage Temperature	-30°C to 60°C																																																																																																																																						
Humidity	5% to 95% RH																																																																																																																																						
Shock	10g																																																																																																																																						
Vibration	10g																																																																																																																																						
EMC	CE																																																																																																																																						
RoHS	CE																																																																																																																																						
REACH	CE																																																																																																																																						
WEEE	CE																																																																																																																																						
Energy Label	CE																																																																																																																																						
Energy Efficiency Class	A																																																																																																																																						
Energy Consumption	0.3W																																																																																																																																						
Energy Consumption per Hour	0.3Wh																																																																																																																																						
Energy Consumption per Day	7.2Wh																																																																																																																																						
Energy Consumption per Month	216Wh																																																																																																																																						
Energy Consumption per Year	2592Wh																																																																																																																																						
Energy Consumption per 1000 Hours	2592Wh																																																																																																																																						
Energy Consumption per 10000 Hours	25920Wh																																																																																																																																						
Energy Consumption per 100000 Hours	259200Wh																																																																																																																																						
Energy Consumption per 1000000 Hours	2592000Wh																																																																																																																																						
Authorised Representative: HANDEHU SHANGHAI SECURITY PRODUCTS MFG. CO., LTD. 1201 Village, Xuyuan Town, Jiangyin District, Suzhou Jiangsu Province, China	Signature: <i>C.M.</i>																																																																																																																																						
Authorised Representative: HANDEHU SHANGHAI SECURITY PRODUCTS MFG. CO., LTD. 1201 Village, Xuyuan Town, Jiangyin District, Suzhou Jiangsu Province, China	Signature: <i>C.M.</i>																																																																																																																																						
Authorised Representative: HANDEHU SHANGHAI SECURITY PRODUCTS MFG. CO., LTD. 1201 Village, Xuyuan Town, Jiangyin District, Suzhou Jiangsu Province, China	Signature: <i>C.M.</i>																																																																																																																																						



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY