

Product Description

□□□□	□□□□□□□□□□□□□□□□□□□□
□□□□□	TM010
□□□□□□□□	□□□□□□□□□□□□□□ PU□□□□□□□□□□
□□□□□□□□	□□□□□□□□□□200□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□ □□□□□□□□□□□□□□
□□□□□□□□	□□□□□□□□□□1100□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□ □□□□□□□□□□□□□□
□□□□□□	D□□□
□□□□	□□□□□□□
□□	□□□□□□PU□□□□□
□□	PU□□□□
□□□	□□□□□□□□
□□□□	□□□□□□□□□□□□□□□□□□□□EVA
□□□	PU□□□
□□□	□□□□
□□□□	38□46□□□
□□□	6 □□
□□□	□□□□/□□□□/□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ 59 x 44 x 33 cm
□□□□□□□□□□	3300□□/ 1x20 '□□□□□ 6600□□/ 1x40□□□□

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY