Product Description

[illegible]	[illegible]
[illegible]	TM2014
[illegible]	[illegible]
[illegible]	[illegible]200[illegible] [illegible]ASTM F2413-18 M I / 75 C / 75[illegible]CE EN ISO 20345[illegible] [illegible]
[illegible]	[illegible]1100[illegible] [illegible]ASTM F2413-18 M I / 75 C / 75[illegible]CE EN ISO 20345[illegible] [illegible]
[illegible]	CE en ISO 20345 SBP SRC[illegible]
[illegible]	D[illegible]
[illegible]	PU[illegible]
[illegible]	PU[illegible]
[illegible]	[illegible]
[illegible]	[illegible]EVA[illegible]Hi-Poly
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	38-46
[illegible]	6 [illegible]
[illegible]	s[illegible]/[illegible]/[illegible]/[illegible]
[illegible]	[illegible]1[illegible]10[illegible]59 x 44 x 33 cm
[illegible]	3300[illegible]/ 1x20 '[illegible] 6600[illegible]/ 1x40 '[illegible]

Product Pictures

TIGER MASTER SAFETY SHOES

Your safety is our concern

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY