Product Description

□□□□	□□□□□□□□□□□□□□□□□□
□□□□□	TM3014
□□□□□□□□□	□□□□□□□□□□□□□□□ PU□□□□□□
□□□□□□□□□	□□□□200□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□
□□□□□□□	□□□□□□1100□□□□□□□□□□□□□□□□□□□□□□□ □ASTM F2413-18 M I / 75 C / 75□CE EN ISO 20345□□□
□□□	CE en ISO 20345 SB-P SRC□□□□□□□
□□□□□	□□□□□□□□□□□□
□□	PU□□□□□
□□	PU□□□□
□□□	□□□□□□□□□□□□□□□□□
□□□□□□	□□□□□□□□□□□□□□□□□□□□□
□□□	PU□□
□□□	□□
□□□□	38-46
□□□	6 □
□□□	s□□□/□□□/□/□□/□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□	□□□□□□□□□□1□□□□□□□□10□□□□□□□□□□□59 x 44 x 33 cm cm.
□□□□□□□	3200□□/ 1x20 '□□□□ 6400□□/ 1x40 '□□□□

Product Pictures

TIGER MASTER SAFETY SHOES

Your safety is our concern

[PRODUCTION PROCESS]

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY