

Product Description

| | |
|----------------|--|
| Modell | TMC4005 |
| Material | isPig isPig |
| Materialstärke | 200 ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 isPig |
| Materialstärke | 1100 ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345 isPig |
| Gewicht | 1.20 kgs / pr |
| Farbe | |
| Farbe | |
| Farbe | |
| Material | PU&isPig |
| Material | EVAHI-POLYPU |
| Material | |
| Material | |
| Material | EUR 38-46 |
| Material | 6 |
| Material | |
| Material | 10/10/10/59 x 44 x 33 cm |
| Material | 3200 / 1x20 'isPig 6400 / 1x40 'isPig |

Product Pictures



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY