

Product Description

Material	High performance polyurethane
Material Code	TMC4006
Material Type	High performance polyurethane High performance polyurethane
Material Properties	High performance polyurethane with 200% elongation ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345
Material Properties	High performance polyurethane with 1100% elongation ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345
Color	Black
Weight	0.15 kg
Weight	0.15 kg
Material	High performance polyurethane
Material	High performance polyurethane
Material	High performance polyurethane HI-POLY PU
Material	High performance polyurethane
Material	High performance polyurethane
Material	EUR 38-46
Material	6
Material	Oil / Water / Acid / Alkali resistant
Material	100% / 100% / 100% / 100% / 58.5 x 40 x 32.5 cm
Material	3300 / 1x20 'Rolls 6600 / 1x40 'Rolls

Product Pictures





SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection