

## Product Description

Model	TMC4008
Material	200µm Polyethylene (PE)
Material Properties	ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345
Material Properties	1100µm Polyethylene (PE)
Material Properties	ASTM F2413-18 M I / 75 C / 75 CE EN ISO 20345
Material Properties	CE en ISO 20345 SBP SRC
Material Properties	
Material Properties	
Material Properties	
Material Properties	Hi-Poly EVA
Material Properties	
Material Properties	
Material Properties	38-46
Material Properties	5.0
Material Properties	s/ / /
Material Properties	1000µm x 1000µm x 58.5 x 40 x 32.5 cm
Material Properties	3300µm / 1x20 ' / 6600µm / 1x40 ' /

## Product Pictures





# SAFETY SHOES TEST



**Toecap Test  $\geq 200$  Joules**



**Midsole Test  $\geq 1200$  Newtons**



**ESD Anti-Static Test**



**Tear Strength  $\geq 120$ N**



**Bondness Test  $\geq 4.0$ N/mm**



**Flex Tester  $\geq 36,000$ T**



# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY