

Product Description

Model:	502
Material:	3D mesh fabric, 3D mesh fabric
Weight:	200 g/m ² . (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 S1) S1 safety toe cap.
Strength:	1100 Newton. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 S1) S1 safety toe cap.
Standard:	CE EN ISO 20345 SBP SRC S1 S2
Color:	Black
Size & Fit:	3d mesh fabric
Weight:	906g
Material:	3D mesh fabric
Sockliner:	EVA foam insole
Color:	Black
Material:	3D mesh fabric
Size:	38-46.
Quantity:	6. Pairs
Material:	3D mesh fabric / 3D mesh fabric / 3D mesh fabric, 3D mesh fabric, 3D mesh fabric, 3D mesh fabric
Dimensions:	10 cm, 10 cm. 3D mesh fabric 58.5 x 40 x 32.5 cm.
Quantity:	3300pairs / 1x20 'pairs' 6600Pairs / 1x40 'pairs'

Product Pictures







F O C U S O N W O R K E R S A F E T Y

TREND PROTECTION FORCE

LIGHT, SOFT, COMFORTABLE,
SMASHING-PROOF AND STAB-PROOF



LIGHTWEIGHT DESIGN

RUBBER FOAM SOLE IS LIGHT AND COMFORTABLE

0 BURDEN, RELEASE YOUR FEET

THE SINGLE (41 YARDS) WEIGHT IS ONLY 405G,
ENJOYING LIGHT AND COMFORTABLE FEET CONTINUOUSLY.



HOLLOW DRAIN DESIGN

THICKENED ELASTIC HOLLOWED-OUT SOLE DESIGN
FOR QUICK DRAINAGE TO ENHANCE GRIP.



WIDEN EUROPEAN STANDARD STEEL HEAD

IT CAN BEAR 200J IMPACT FORCE OR 15KN STATIC PRESSURE, AND IS WIDENED BY 2MM WITHOUT GRINDING FEET.



KEVLAR STAB PROOF MIDSOLE

KEVLAR FLEXIBLE MIDSOLE, EFFECTIVE PUNCTURE RESISTANCE \geq 1100N, AND FOOT SAFETY



SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY