

Product Description

| | |
|-------------------|--|
| Material: | Non-woven fabric |
| Model: | 605. |
| Material: | Non-woven fabric 3D, Non-woven fabric |
| Material: | Non-woven fabric 200 gsm. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345) Non-woven fabric. |
| Material: | Non-woven fabric 1100 Newton gsm. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345) Non-woven fabric. |
| Material: | CE EN ISO 20345 SBP SRC Non-woven fabric |
| Material: | Non-woven fabric |
| Material & Color: | 3d Non-woven fabric |
| Material: | Non-woven fabric 730g |
| Material: | Non-woven fabric |
| Sockliner: | Non-woven EVA Non-woven fabric |
| Material: | Non-woven fabric |
| Material: | Non-woven fabric |
| Material: | Non-woven fabric 38-46. |
| Material: | 6. Non-woven fabric |
| Material: | Non-woven fabric / Non-woven fabric / Non-woven fabric, Non-woven fabric, Non-woven fabric, Non-woven fabric |
| Material: | Non-woven fabric 1, Non-woven fabric 10. Non-woven fabric 58.5 x 40 x 32.5 cm. |
| Material: | 3300pairs / 1x20 'Non-woven fabric' 6600Pairs / 1x40 'Non-woven fabric' |

Product Pictures



PUNCTURE RESISTANT



IMPACT RESISTANT



SUPER LIGHT



Huade®

重量

0.0363

克

去皮

单位

交流

置零

去皮

上海华德衡器有限公司





SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



Bondness Test ≥ 4.0 N/mm



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY