Product Description

	CE 00 00 000 00 00 00 00 00 00
00 00:	BTA050
00 0 00 :	Nubuck [][] & [][][] PU / PU [][] [][] []
000 0 :	□□ □□□□□ 200 □□ □□□□ □□□□. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□) Non □□ □□□□□.
000:	□□□ □ □□ □□ □□ □□□ 1100 □□. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□) Non □□ □□□□□.
<u> </u>	CE
000:	
<u> </u>	
<u></u> :	
<u> </u>	
<u> </u>	□□ EVA □□ HI-POLY □□ PU
<u> </u>	PU [[
<u> </u>	EUR 37-47
<u> </u>	6 🖂
<u> </u>	
<u> </u>	Metal free, s[] / [] / [] / [] [] [] [] [] [] [] [] [] [] [] [] []
000:	1 pair per color box, 10 pairs □□ □. Carton size□58.5 x 40 x 32.5 cm
0000 000 :	3200pairs / 1x20 '□□□□ 6400pairs / 1x40'□□□□

Product Pictures





Production Process



SAFETY SHOES TEST





Toecap Test≥200 Joules



Midsole Test≥1200 Newtons



ESD Anti-Static Test



Tear Strength ≥120N



Bondness Test ≥4.0N/mm



Flex Tester ≥ 36,000T

Canton Fair





SAFETY SHOES



RAIN BOOTS





PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY