

Product Description

□□□:	2020 □□□ □□ □□ □□ □□□ □□
□□ □□:	ETPU39
□□ □ □□ :	□□□□ □□ 3D □□□ □□ □□ □□, PU / PU □ ETPU □□
□□□ □□ :	□□□ □□ 200J□ □□ □□. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□) □□ □□□□.
□□ □ :	□□ □□ 1100 □□□ □□□ □□ □□ □□ □. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□) □□ □□□□.
□□□:	□□□ □□ □□ □□□
□□:	3D □□□ □□ □□
□:	□□□ □□
□□:	□□□ □□ □□ □□
□□ :	□□ EVA □□ HI-POLY □□ PU
□□:	PU □□
□□:	□□ □□
□□:	38 ~ 46 □□
□□:	6 □□
□□:	□□ □□, s□□ / □□ / □□ / □□ □□, □□□ □□, □□ □□
□□□:	□□ □□ □ 1 □ □, □□ □ 10 □ □. □□ □□□ 58.5 x 40 x 32.5cm
□□□□□ □□□ :	3200pairs / 1x20 '□□□□ 6400pairs / 1x40'□□□□

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY