

## Product Description

□□□:	□□□ □□□ □□□ □□ □□ □□ □□ □□ □□ □□
□□ □□:	ETPU40
□□ □ □□ :	□□ □□, PU / PU □□ □□ □□
□□□ □□ :	□□□ □□ 200 □□ □□ □□. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□) □□ □□□□.
□□ □ :	□□ □□ 1100 □□□ □□□ □□ □□ □□ □. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□) □□ □□□□.
□□□:	□□□ □□ □□ □□□
□□:	□□□ □□□□ □□
□:	□□□ □□□□ □□
□□:	□□□ □□ □□□□ □□ □□
□□ :	□□ EVA □□ HI-POLY □□ PU
□□:	PU □□
□□:	□□ □□
□□:	38 ~ 46 □□
□□:	6 □□
□□:	□□ □□, s□□ / □□ / □□ / □□ □□, □□□ □□, □□ □□
□□□:	□□ □□ □ 1 □ □, □□ □ 10 □ □. □□ □□□ 58.5 x 40 x 32.5cm
□□□□□ □□□ :	3200pairs / 1x20'□□□□ 6400pairs / 1x40'□□□□

## Product Pictures





# Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

# SAFETY SHOES TEST



**Toecap Test  $\geq 200$  Joules**



**Midsole Test  $\geq 1200$  Newtons**



**ESD Anti-Static Test**



**Tear Strength  $\geq 120$ N**



**Bondness Test  
 $\geq 4.0$ N/mm**



**Flex Tester  $\geq 36,000$ T**

# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY