Product Description

□□□:	□□□ □□□ □□□ □□ □□ □□□ □□ □□ □□ □□□
□□ □□:	ETPU40
□□ □ □□ :	□□ □□, PU / PU □□ □□ □□
□□□ □□ :	□□□ □□ 200 □□ □□ □□. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□) □□ □□□□□.
□□ □ :	□□ □□ 1100 □□□ □□□ □□ □□ □□ □. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□) □□ □□□□□.
□□□:	□□□ □□ □□ □□□
□□:	□□□ □□□□ □□
□:	□□□ □□□□ □□
□□:	□□□ □□ □□□□ □□ □□
□□ :	□□ EVA □□ HI-POLY □□ PU
□□:	PU □□
□□:	□□ □□
□□:	38 ~ 46 □□
□□:	6 □□
□□:	□□ □□, s□□ / □□ / □□ / □□ □□, □□□ □□, □□ □□
□□□:	□□ □□ □ 1 □ □, □□ □ 10 □ □. □□ □□□ 58.5 x 40 x 32.5cm
□□□□□ □□□ :	3200pairs / 1x20 '□□□□ 6400pairs / 1x40’□□□□

Product Pictures

OIL RESISTANT
SLIP RESISTANT

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY