

Product Description

000:	000 EVA 0 00 000 00 00 000
00 00:	TMC4003
00 0 00 :	00 : 00 000 3D 00 00 000 000 : EVA
000:	1. 00 00 00 00 00 0 0 000 200 0. 2. 00 00000.
000 :	1. Kevlar mid sole 1100N. 2. 00 00000.
00 & 0 :	0000 00
00:	0.76 kgs per 0
00:	0000 00, 00 000, 000 00 0000 00000.
00 :	00 EVA 00 HI-POLY 00 PU, 00 00 00 & 00 00 00
00:	000
00:	00 00
00:	EUR 36-46 (US 2-12)
00:	CE EN ISO 20345 SB-P SRC 00 00
00:	6 00
000:	00 00 0 1 0, 00 0 10 0.
00 00	58.5x40x32.5cm
00000 000 :	3300pairs / 1x20 '00000 6600pairs / 1x40'00000

Product Pictures







SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

SHOES MATERIALS



Genuine Cow Leather



CE Steel Toecap



CE Steel Plate



Composite Toecap



Different Eyelets



Durable Lace



Breathable Lining



Comfortable Insoles



PU or RUBBER or TPU soles

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY