## **Product Description**

000:	000 EVA 0 00 000 00 000
	TMC4003
00 0 00 :	00 : 00 000 3D 00 00 000 000 EVA
	1. 00 00 00 00 0 00 0 00 00 000 200 0.
	2. 00 00000.
000:	1. Kevlar mid sole∏ 1100N.
	2. 00 00000.
□□ & □ :	
<u> </u>	0.76 kgs per □
<u> </u>	
:	□□ EVA □□ HI-POLY □□ PU, □□ □□ □□ & □□ □□
00:	
DD:	
	EUR 36-46 (US 2-12)
<u> </u>	CE EN ISO 20345 SB-P SRC [] []
<u> </u>	6 🖂
000:	
00 00	58.5x40x32.5cm
00000 000 :	3300pairs / 1x20 '\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \

**Product Pictures** 







# **SAFETY SHOES TEST**





Toecap Test≥200 Joules



Midsole Test≥1200 Newtons



**ESD Anti-Static Test** 



Tear Strength ≥120N



Bondness Test ≥4.0N/mm




Flex Tester ≥ 36,000T

## **SHOES MATERIALS**






















# Canton Fair





#### SAFETY SHOES



### **RAIN BOOTS**





PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY