Product Description

□□□:	□□□ □□ □□ □□ □□ □□□□ □□□□ □□□ □□ □□□
□□ □□:	SJ0222
□□ □ □□ :	□□□ □□□ TPU, □□ PU □□ □□ PU / PU □□ □□
□□□ □□ :	□□ □□ (□□ □□ □□)□ □ □□□□ 200 □□□□. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□) □ □□ □□□□ □□□□□.
□□ □ :	□□ □□□□ 1100 □□ □ □□ (□□ □□□ □□ □□ □□). (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 □□) □ □□□ □□□□□.
□□ □□ :	D □
□□□:	□□□ □□ □□ □□□
□□:	PU □□ □□
□:	PU □□ □□
□□:	□□□ □□ □□ □□
□□ :	□□ EVA □□ HI-POLY □□ PU
□□:	PU □□
□□:	□□ □
□□:	37 ~ 47 □□
□□:	6 □□
□□:	□□□□ / □□ / □□ / □□ □□, □□□ □□, □□, □□ □□
□□□:	□□ □□ □ 1 □ □, □□ □ 10 □ □. □□ □□□ 59 x 44 x 33cm
□□□□□ □□□ :	3300pairs / 1x20 '□□□□ 6600pairs / 1x40’□□□□

Product Pictures

TIGER MASTER

ABSORBER

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY