

## Product Description

CE:	CE 00 0000 00 0000 00 0000 0000
SMR:	SMR10
PU / PU:	0000 00 00 PU / PU 00 00
ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 0000:	0000 00 200J 00 00. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 0000) 00 000000.
ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 0000:	00 00 1100 0000 0000 00 00 00 0. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 0000) 00 000000.
CE:	CE
0000:	0000 00
00:	0000 00
0000:	0000 00 00 00
00 :	00 EVA 00 HI-POLY 00 PU
PU:	PU 00
00:	00 00
38 ~ 46:	38 ~ 46 00
6:	6 00
00 00, s00 / 00 / 00 / 00 00, 0000 00, 00, 00 00:	00 00, s00 / 00 / 00 / 00 00, 0000 00, 00, 00 00
00 00 0 1 0 0, 00 0 10 0 0. 00 0000 58.5 x 40 x 32.5cm:	00 00 0 1 0 0, 00 0 10 0 0. 00 0000 58.5 x 40 x 32.5cm
3200pairs / 1x20 '000000 6400pairs / 1x40'000000:	3200pairs / 1x20 '000000 6400pairs / 1x40'000000

## Product Pictures





# Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection



# SAFETY SHOES TEST



**Toecap Test  $\geq 200$  Joules**



**Midsole Test  $\geq 1200$  Newtons**



**ESD Anti-Static Test**



**Tear Strength  $\geq 120$ N**



**Bondness Test  
 $\geq 4.0$ N/mm**



**Flex Tester  $\geq 36,000$ T**

# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY