

Product Description

CE:	CE 00 00 00 0000 00 0000 00 0000 00
SMR:	SMR12H
PU / PU :	0000 00 00, PU / PU 00 00 0
ASTM :	0000 00 200J 00 00. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 00) 00 000000.
EN ISO :	00 00 1100 0000 0000 00 00 00 0. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 00) 00 000000.
CE:	CE
000:	0000 00
00:	0000 00
000:	0000 00 00000 00 00
00 :	00 EVA 00 HI-POLY 00 PU 00 0000 00 0 00 0 0000 00 00000.
PU:	PU 00
00:	00 00
00:	38 ~ 46 00
00:	6 00
00:	00000 / 00 / 00 / 00 00, 0000 00, 00, 00 00,
0000:	00 00 0 1 0 0, 00 0 10 0 0. 00 0000 59 x 44 x 33cm
000000 0000 :	3200pairs / 1x20'000000 6400pairs / 1x40'000000

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY