

Product Description

CE:	CE 符合 EN ISO 20345 标准
鞋型:	SMR13
鞋面材料:	PU / PU 鞋面
鞋面厚度:	鞋面厚度 200 毫米。 (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 标准) 符合 EN ISO 20345 标准。
鞋底厚度:	鞋底厚度 1100 毫米。 (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 标准) 符合 EN ISO 20345 标准。
鞋跟:	CE
鞋头:	鞋头
鞋跟:	鞋跟
鞋面:	鞋面 符合 EN ISO 20345 标准
鞋面材料:	鞋面 EVA 鞋面 HI-POLY 鞋面 PU 鞋面 符合 EN ISO 20345 标准。
鞋面:	PU 鞋面
鞋面:	鞋面
鞋面:	38 ~ 46 毫米
鞋面:	6 毫米
鞋面:	鞋面 / 鞋面 / 鞋面 鞋面, 鞋面 鞋面, 鞋面, 鞋面 鞋面,
鞋面:	鞋面 鞋面 1 毫米, 鞋面 10 毫米。鞋面 鞋面 58.5 x 40 x 32.5cm
鞋面材料:	3200pairs / 1x20'鞋面 6400pairs / 1x40'鞋面

Product Pictures







Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY