

Product Description

000:	00000 0000 000 00 000 00 000 000 00 00 00
00 00:	SRS006
00 00 :	00 : 00 0 0000 00 000 : 00 00 (0000)
000:	1. 00 00 0 (00 0000 00) 000 200j
	2. 00 00000.
000 :	1. 00 0000 1100 00 000 000 00 00 000.
	2. 00 00000.
00:	0000 0000 00
0:	PU 00 00
0:	00 00 0 000 0000 00 000
00 000 :	00 00 000 00 HI-POLY 00 PU 00 0 00 EVA
00:	000
00:	00 00
00:	EUR 36-46 (00 2-12)
00:	CE EN ISO 20345 S1-P 00 00
00:	6 00
000:	00 0 00 00, 00000 10 0
00 00	58.5x40x32.5 00 00
00000 00 00 :	3300 0 / 1x20 '00000 6600 0 / 1x40 '00000

Product Pictures





SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

