

Product Description

000:	000 00 00 0000 00 00 000 000 000 00
00 00:	SRS01H
00 00 :	00 : 00 0 0000 00 000 : 00 00
000:	1. 00 000 200 00 000 0000. 2. 00 00000.
000 :	000
00:	0000 00
0:	PU 00 00
00:	00 0000 00 0000 00 0000 00000.
00 :	00 EVA 00 HI-POLY 00 PU, 0000 0000 00 0 00 0 00 00
00:	00 00
00:	36-46
00:	CE EN ISO 20345 SB SRC 00 00
00:	00 / 00 / 00 / 00 00, 000 00, 00 00, 00 00
00 :	000
00:	6 00
000:	00 00 0 1 0 0, 00 0 10 0 0.
00 00	59x44x33 00 00
00000 00 00 :	3200 0 / 1x20 '00000 6400 0 / 1x40 '00000

Product Pictures







SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



Bondness Test ≥ 4.0 N/mm



Flex Tester $\geq 36,000$ T

SHOES MATERIALS



Genuine Cow Leather



CE Steel Toe cap



CE Steel Plate



Composite Toe cap



Different Eyelets



Durable Lace



Breathable Lining



Comfortable Insoles



PU or RUBBER or TPU soles

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY