

Product Description

toecap:	toecap
TM010:	TM010
PU:	PU
200:	200 (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345) 200
1100:	1100 (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345) 1100
D:	D
toecap:	toecap
PU:	PU
toecap:	toecap
toecap:	toecap
EVA:	EVA
PU:	PU
toecap:	toecap
EUR 38-46:	EUR 38-46
6:	6
toecap:	toecap
59x44x33:	59x44x33
3300 / 1x20 'toecap':	3300 / 1x20 'toecap' 6600 / 1x40 'toecap'

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY