# **Product Description**

	600 00 00 00 000 00 00 00 00 0000
00 00:	TM114
00 0 0:	□□: □□ □□ □□: PU/ PU □□ □□ □
	1. 00 00 0 0000 200 0. 00 00 000 00000.
	2. non 🛮 🖂 🖂 🗀 .
<u> </u>	1. 00 00 1100 000 00 0000. 000 0000 000
	2. non 🛮 🖺
<u> </u>	PU [] []
□:	
OD:	
	000 HI-POLY 00 0000 (00000 0 00 &000 00 00000.)
	PU [[
□:	6
<u></u> :	38-46
□□:	CE EN ISO 20345:2011 S3 SRC [[[[[]]]]].
0000:	12 00 000 000 000 0 6 00 000 000 000 00 000 0
	c[] 1 [] olor [] [] [] [] [] [] 10 [].
00 00	65 x 54 x 35 cm
0000 000:	2600[/1×20" [][][] 5200[]/1×40 [][][]

## **Product Pictures**







SLIP- SHOCK RESISTANT ABSORPTION







ANTI-STATIC PETROL AND CHEMICAL RESISTANT



ANTI-NAIL MIDSOLE



OIL RESISTANT





# **PACKING**





## **COMPANY INFORMATION**

# **TIGER MASTER**







#### **TIGER MASTER OFFICE SHOW**





## **TIGER MASTER SAMPLE ROOM**





# **SAFETY SHOES TEST**





Toecap Test≥200 Joules



Midsole Test≥1200 Newtons



**ESD Anti-Static Test** 



Tear Strength ≥120N



Bondness Test ≥4.0N/mm



Flex Tester ≥ 36,000T

# **Production Process**



# PERSONAL PROTECTIVE EQUIPMENT WORK SAFETY SOLUTION PROVIDER























