

Product Description

| | |
|------------|--|
| Model: | TM216G-L. |
| Material: | Upper : PU / PU Insole : PU / PU |
| Weight: | 1. 200g per pair 2. 200g per pair |
| Length: | 1. 1100mm insole 2. 1100mm |
| Color: | Black |
| Material: | PU |
| Material: | PU (Upper & Insole) |
| Sockliner: | PU insole - PU insole (Upper & Insole) |
| Material: | PU |
| Material: | PU |
| Material: | 37-47. |
| Material: | CE EN ISO 20345 : 2011 S1-P SRC |
| Material: | 6 |
| Material: | C 1 color, 10 |
| Material: | 58.5 x 40 x 32.5 cm. |
| Material: | 3300pairs / 1x20 6600Pairs / 1x40 |

Product Pictures





[PRODUCTION PROCESS]



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY