

Product Description

Model:	TM5003
Material:	Upper is Split nubuck leather EVA & Rubber
Weight:	200g (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 (S)) Non-slip.
Weight:	1100g (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 (S)) Non-slip.
Weight:	1.30 kgs / pr
Weight:	100g
Weight:	100g
Weight:	100g
Weight:	100g
Weight:	100g
Weight:	EVA Rubber
Weight:	100g
Weight:	100g
Weight:	EUR 38 ~ 46
Weight:	100g
Weight:	100g / 100g / 100g, 100g, 100g, 100g, 100g.
Weight:	1 pair per color box, 10 pairs per box. Carton size: 59 x 44 x 33 cm
Weight:	3200pairs / 1x20'boxes 6400pairs / 1x40'boxes

Product Pictures





SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY