## Product Description

| | |
|---|---|
| □□□: | □□□ □□□ □□ □□ □□ □□ □□ |
| □□ □□: | TM112 |
| □□□ □□ : | □□□ □□□ □ □□□ □ □□□□□<br>□□□ □□ □□□□ □□□ □□ □□□□. |
| □□□ □ : | □□ □□□ □ □□ □□ □□□ □□ □□ □□□ 200 □□□□□□.<br>(ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 □□)<br>□□ □□□□□. |
| □□ □□ : | □□ □□□□ □□ □□□ □-□□ □□□ □□ □□□ 1100 □□□ □ □□□□.<br>(ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 □□)<br>□□ □□□□□. |
| □□: | 1.20 kgs/pr |
| □□: | □□□ |
| □□: | PU □□ □□ |
| □: | PU □□ □□ |
| □□: | □□□ □□ □□□□ □□ □□□ |
| □□ □□□ : | □□ □□□ □□ □□□ □□ □ □□ EVA |
| □□: | PU □□ |
| □: | □□ □ |
| □□: | EUR 38-46 |
| □□□□: | 6 □ |
| □□: | □□IL/□/□□/□□/□□ □□, □□ □□, □□ □ □□ □□ □□ □□. |
| □□□: | □□ □□ □ 1 □, □□ □ 10 □. □□ □□□□□59 x 44 x 33 cm |
| □□□□□ □□□ : | 3200Pairs /1x20 '□□□□<br>6400Pairs /1x40 '□□□□ |

## Product Pictures

# SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N



Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

# Canton Fair

## SAFETY SHOES

## RAIN BOOTS

**PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY**

# Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods