

Product Description

| | |
|---------------|---|
| 000: | 00 00 00 00 00 00 00 00 00 00 00 |
| 00 00: | TMC043 |
| 00 00 : | 00 : 000 3D 000 00 00 000 : EVA & 00 (MD 000) |
| 000: | 1. 0 0000 000 00 000 0 200 0. 2. 00 00000. |
| 000 : | 1. Kevlar 0000 1100 000 00 0000 0000. 2. 00 00000. |
| 00: | 000 3D 000 00 00 |
| 0: | 000 00 |
| 0: | 0000 00 0 00 00 000 |
| 00 000 : | 00 EVA 00 HI-POLY 00 PU, 0000 0000 00 0 00 0 00 00 |
| 00: | 000 |
| 00: | 00 00 |
| 00: | EUR 36-46 (00 2-12) |
| 00: | CE EN ISO 20345 S1-P SRC 00 00 |
| 00: | 6 00 |
| 000: | 00 00 0 1 0 0, 00 0 10 0 0. |
| 00 00 | 58.5x40x32.5 00 00 |
| 00000 00 00 : | 3300 0 / 1x20 '00000 6600 0 / 1x40 '00000 |

Product Pictures





Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

SHOES MATERIALS



Genuine Cow Leather



CE Steel Toecap



CE Steel Plate



Composite Toecap



Different Eyelets



Durable Lace



Breathable Lining



Comfortable Insoles



PU or RUBBER or TPU soles