

Product Description

Productnaam:	China lederen stalen neus bouwplaats veiligheidsschoenen S1P
Item nr:	DTA032
Bovenste en enige:	Bovenwerk: glad rundleer Zool: PU dubbele dichtheid
Teen:	1. Stalen neus, deze kan 200 Joule slagvast zijn. 2. non wordt ook verstrekt.
Tussenzool:	1. Stalen plaat, het kan zijn prik resistant 1100 newton. 2. Niet is ook voorzien
Gewicht:	1,2 kg / pr
Halsband:	Oxford stof met hoge dichtheid en spons
Tong:	Oxford stof met hoge dichtheid
Voering:	Zwart lucht- en droog sandwichweefsel (je voeten blijven droog en comfortabel)
sockliner:	Gegoten EVA of HI-POLY of PU (verminder uw pijn en vermoeidheid door dagelijks werk aanzienlijk)
Bouw:	PU-injectie
Hoogte:	Lage enkel
Grootte:	37-47 (3-13)
Standaard:	CE EN ISO 20345 S1P SRC of andere als uw vereisten
Garantie:	6 maanden
Pakket:	1 paar per color binnendoos verpakking, 10 paar per doos.
Grootte van het karton	58,5 x 40 x 32,5 cm
Laad hoeveelheid Container:	3300pairs / 1x20 'container 6600pairs / 1x40 'container

Product Pictures





Company Information



Intertek

EC Type Examination Certificate



Issued to: FUJIAN HONGJIAN SHISE CO., LTD.
SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NANJI
3211, ZHOUJIAN PROVINCE, CHINA

Authorised Representative: HANDEHU SHANGHAI PRODUCTIVE APPL. CO., LTD.
1201 Village, Xuyuan Town, Jiangyin District, Suzhou,
Henanjiang Province, China

Date of Issue: 11 January 2018

Expiry Date: 11 February 2020

Certificate No.: L20170002947 (extension of certificate L20170294719)

Product Reference(s): Safety Group:
48501-48502
48503-48504
48505-48506
48507-48508
850-200-300-350

Description:

Construction:	Indoor
Topology:	Open ended
Material:	Open wire
Core:	Steel
Wire:	600 (PVC)
Shield:	ACU
Shielding:	Non-magnetic Fe
Core Range:	30-45
Category:	850-350

Authorized Representative: *C.M.* 1687-0218

Product Reference: 1687-0218

Issued by: Intertek Testing Services (UK) Limited



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY