

Product Description

Productnaam:	Tijgermerk lederen lederen veiligheidsschoenen stalen neus
Item nr:	DTA032H
Bovenste en enige:	Bovenwerk: glad rundleer Zool: PU dubbele dichtheid
Teen:	1. Stalen neus, deze kan 200 Joule slagvast zijn. 2. non wordt ook verstrekt.
Tussenzool:	1. Stalen plaat, het kan zijn prik resistent 1100 newton. 2. Niet is ook voorzien
Gewicht:	1,2 kg / pr
Halsband:	Oxford stof met hoge dichtheid en spons
Tong:	Oxford stof met hoge dichtheid
Voering:	Zwart lucht- en droog sandwichweefsel (je voeten blijven droog en comfortabel)
sockliner:	Gegoten EVA of HI-POLY of PU (vermindert uw pijn en vermoeidheid door dagelijks werk aanzienlijk)
Bouw:	PU-injectie
Hoogte:	Hoge enkel
Grootte:	37-47 (3-13)
Standaard:	CE EN ISO 20345 S1P SRC of andere als uw vereisten
Garantie:	6 maanden
Pakket:	1 paar per color binnendoos verpakking, 10 paar per doos.
Grootte van het karton	59 x 44 x 33 cm
Laad hoeveelheid Container:	3200 paar / 1x20 'container 6400pairs / 1x40 'container

Product Pictures





Company Information



Intertek

EC Type Examination Certificate

CE

Issued to: FUJIAN HONGJIAN SHISECO LTD.
SHANGHAI INDUSTRIAL ZONE, JINCHANG TOWN, NINGBO
321117, ZHEJIANG PROVINCE, CHINA

Authorised Representative: HANDEHU SHANGHAI PRODUCTIVITY APC (S) LTD.
1201 Village, North Town, Jiangyin District, Suzhou,
Hubei Province, China

Date of Issue: 11 January 2018

Expiry Date: 11 February 2020

Certificate No.: L20170002947 (extension of certificate L20170294719)

Product Reference(s): Safety Plug:
480V-10A/15A
480V-16A/20A
480V-18A/25A
480V-20A/32A
850-20A-30A-50A

Description:
Construction: Thermoplastic
Type: 2P+E+N+PE
Material: PVC
Core: 2000 (PVC)
Wire: PVC
Mount: ACS
Type Marking: 2P+E+N+PE
Type Range: 20A-50A
Category: 500V-10A

Signature: *C.M.* 16/1/2018

Printed: 16/1/2018

Location of Issuance: 115, West 17th Street, 11th Floor, Suzhou, China

Intertek



Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY