

Product Description

Productnaam:	Lage enkel TPU-zool, antislip stalen neus, prikbestendige werkschoenen
Item nr:	JK014
Boven- en zool:	Bovenwerk van microfiber leer Zool van PU en TPU
Teenkap:	Stalen neus om schokbestendig te zijn 200 joule. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 standaard) Er is ook een niet-stalen neus aanwezig.
Middenzool:	Niet-metalen anti-penetratie middenzool om perforatiebestendig te zijn 1100 Newton. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345 standaard) Niet-stalen plaat is ook aanwezig.
Gewicht:	525 gram per stuk
Kant:	Duurzame platte veterschoen
Halsband:	PU-kunstleer met spons
Tong:	Mesh stof met hoge dichtheid
Voering:	Air mesh stof
Inlegzolen:	Gegoten EVA of HI-POLY of PU
Bouw:	PU-injectie
Hoogte:	Lage enkel
Grootte:	EUR 38-46
Garantie:	6 maanden
Functie:	Slip / olie / impact / perforatiebestendig, antistatisch, waterdicht, schokabsorptie
Pakket:	1 paar per verfdoo, 10 paar per doos. Grootte van het karton is 58,5 x 40 x 32,5 cm
Laad hoeveelheid container:	3300 paar / 1x20 'container 6600 paar / 1x40 'container

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY