

Product Description

Productnaam:	Slijtvaste, oliebestendige veiligheidslaarzen van echt leer
Item nr:	PR001
Bovenwerk en zool:	Bovenwerk van echt leer PU & rubberen zool
Neus:	Samengestelde neus om slagvast te zijn 200 joule. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345-norm) Er is ook een niet-stalen neus.
Tussenzool:	Niet-metalen anti-penetratie inlegzolen om lekbestendig te zijn 1100 newton. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345-norm) Er wordt ook niet-stalen plaat geleverd.
Stijl:	Geregen
Kant:	Duurzame ronde schoenveters
Halsband:	PU-kunstleer met spons
Tong:	Echt leer van PU
Voering:	Air mesh stof
Inlegzool:	Gegoten EVA of HI-POLY of PU
Bouw:	PU-injectie
Hoogte:	Hoge enkel
Grootte:	EUR 38-46
Garantie:	6 maanden
Functie:	slip / olie / impact / prikbestendig, antistatisch, waterdicht, schokabsorberend, slijtvast.
Pakket:	1 paar per verfdoo, 10 paar per doos. Grootte van het karton is 59 x 44 x 33 cm
Laadhoeveelheid container:	3200pairs / 1x20 'container 6400 paar / 1x40 'container

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY