Product Description

Productnaam:	Slijtvaste, oliebestendige veiligheidslaarzen van echt leer
Item nr:	PR001
Bovenwerk en zool:	Bovenwerk van echt leer PU & rubberen zool
Neus:	Samengestelde neus om slagvast te zijn 200 joule. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345-norm) Er is ook een niet-stalen neus.
Tussenzool:	Niet-metalen anti-penetratie inlegzolen om lekbestendig te zijn 1100 newton. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345-norm) Er wordt ook niet-stalen plaat geleverd.
Stijl:	Geregen
Kant:	Duurzame ronde schoenveters
Halsband:	PU-kunstleer met spons
Tong:	Echt leer van PU
Voering:	Air mesh stof
Inlegzool:	Gegoten EVA of HI-POLY of PU
Bouw:	PU-injectie
Hoogte:	Hoge enkel
Grootte:	EUR 38-46
Garantie:	6 maanden
Functie:	slip / olie / impact / prikbestendig, antistatisch, waterdicht, schokabsorberend, slijtvast.
Pakket:	1 paar per verfdoos, 10 paar per doos. Grootte van het karton is 59 x 44 x 33 cm
Laadhoeveelheid container:	3200pairs / 1x20 'container 6400 paar / 1x40 ’container

Product Pictures

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY