

## Product Description

Product Name:	
Item No:	TM007
Upper and Sole:	Embossed split cow leather PU/ PU dual density
Toe cap:	Steel toe to be impact resistant 200 joules. (ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 standard) Non is also provided.
Mid sole:	Steel plate to be puncture resistant 1100 newton. (ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 standard) Non is also provided.
Standard:	CE EN ISO 20345:2011 S3 SRC
Style:	laced up safety shoes
Collar:	High density oxford fabric
Tongue:	High density oxford fabric
Lining:	Breathable air mesh fabric
Sockliner:	Moulded EVA coated with air mesh fabric or others
Construction:	PU injection
Size:	EUR 37-47
Guarantee:	6 months
Usage:	construction site, mining, industrial, general working etc.
Function:	S lip/ oil/ impact/ puncture resistant, anti static, waterproof, shock absorption
Package:	1 pair per color box, 10 pairs per carton. Carton size is 59 x 44 x 33 cm
Load quantity of Container:	3200pairs /1x20" container 6400pairs /1x40 container

## Product Pictures



TIGER MASTER  
SHOES  
ALWAYS OUR CONCERN

more SAFE  
STYL  
COMFOR

TIGER MASTER  
SHOES



# TIGER MASTER SAFETY SHOES

YOUR SAFETY IS OUR CONCERN

**HOT SALES**



STEEL  
TOE CAP



PUNCTURE RESISTANT  
STEEL



ANTI-STATIC  
SHOE



SLIP RESISTANT  
SOLE



OIL AND FUEL  
RESISTANT SOLE



**CE EN ISO 20345 S1P SRC**

**SHOW**

DETAIL DISPLAY

- ***Water resistant embossed split cow leather***



- **TIGER MASTER BRAND**



- **HIGH DENSITY OXFORD FABRIC**



# TIGER MASTER SAFETY SHOES

Your safety is our concern



**Steel toe cap**  
**Impact resistant**

**Comfortable Insoles**  
**Breathable**



**PU dual density sole**  
**Oil & slip resistant**

**Steel plate**  
**Puncture Resistant**

# Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

# Canton Fair



## SAFETY SHOES



## RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY