

Product Description

Productnaam:	CE stalen neus punctiebestendige Europese veiligheidsschoenen
Item nr:	SD5067
Boven- en zool:	Reliëf rundleer PU dubbele dichtheid
Teen:	1. Stalen neus om schokbestendig te zijn 200 joule. (ASTM F2413-05 M I / 75 C / 75, CE ENISO 20345 STANDARD, een verscheidenheid aan passend kiezen uit)
	2. niet-stalen neus is ook aanwezig.
bord :	1. Stalen plaat om lekbestendig 1100 Newton te zijn. (ASTM F2413-05 M I / 75 C / 75, CE ENISO 20345 STANDAARD, een verscheidenheid aan montage om uit te kiezen)
	2. niet-stalen plaat is ook aanwezig
Halsband:	PU-kunstleer
Tong:	PU-kunstleer, zandbestendig
Voering:	Air & dry mesh stof
Inlegzool:	Voorgevormd EVA bekleed met mesh stof
Bouw:	PU-injectie
Hoogte:	Hoge enkel
Grootte:	EUR 37-47
Garantie:	6 maanden
Pakket:	Kleur binnendoos verpakking, 10 paar in een doos
Pakket:	1 paar per verfdoo, 10 paar per doos. Grootte van het karton is 59 x 44 x 33 cm
Laad hoeveelheid container:	3300 paar / 1x20 'container 6600 paar / 1x40 'container

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY