

Product Description

Productnaam:	PU-injectie sport veiligheidsschoenen
Item nr:	SP028
Bovenwerk en zool:	Luchtdoorlatende 3D vliegende gebreide stof PU / PU dubbele dichtheid
Neus:	Stalen neus om slagvast te zijn 200 joule. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345-norm) Niet is ook voorzien.
Tussenzool:	Stalen plaat om lekbestendig te zijn 1100 newton. (ASTM F2413-18 M I / 75 C / 75, CE EN ISO 20345-norm) Niet is ook voorzien.
Stijl:	Geregen
Halsband:	3D vliegende gebreide stof
Tong:	Mesh stof met hoge dichtheid
Voering:	Ademende mesh-stof
Inlegzool:	Voorgevormde EVA gecoat met luchtgaasweefsel of andere
Bouw:	PU-injectie
Hoogte:	Lage enkel
Grootte:	EUR 38-46
Garantie:	6 maanden
Functie:	Slip / olie / impact / lekbestendig, antistatisch, schokabsorptie
Pakket:	1 paar per verfdoo, 10 paar per doos. Grootte van het karton is 58,5 x 40 x 32,5 cm
Laadhoeveelheid container:	3300pairs / 1x20 'container 6600 paar / 1x40 'container

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY