

Product Description

Productnaam:	S3 SRC hoge riggerlaarzen
Item nr:	TM5009
Bovenste en zool:	Bovenkant: reliëf gespleten koe leer Sole: PU / PU Dual Density Sole
Teen:	1. Steel Teen Cap om slagbestendig 200 joules te zijn. 2. Niet-stalen neus is ook aanwezig.
Midsole:	1. Stalen plaat om prikbestendig 1100 Newton te zijn. 2. Niet-stalen plaat wordt ook verstrekt
Kraag en tong:	Geen kraag
stijl:	Geen laklaarzen
Voering:	Air Mesh-stof (het wordt uw voeten comfortabel gehouden)
Sockliner:	Antistatische gevormde EVA gecoat met luchtgasstof of anderen als uw vereisten (vermindert u uw voeten en vermoeidheid van dagelijks werk)
Bouw:	PU-injectie
Hoogte:	29-30 cm
Grootte:	38-47
Standaard:	CE EN ISO 20345: 2011 S3P SRC
Garantie:	6 maanden
Pakket:	Kleur binnendoos verpakking, 10 paren in een doos.
Kartongrootte	68 x 65 x 34,5 cm
Laadhoeveelheid van de container:	1800 pairs / 1x20 'container 3600pairs / 1x40 'container

Product Pictures





Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T