

Product Description

Productnaam:	metaalvrije composiet teen antistatische waterdichte laslaarzen voor lassers
Item nr:	W1018
Boven- en zool:	Split gek paardenleer en TPU-bovenwerk, PU- en rubberen zool
Teenkap:	1. Composiet neus om schokbestendig te zijn 200 joule. (ASTM F2413-05 M I / 75 C / 75, CE ENISO 20345 STANDARD, een verscheidenheid aan passend kiezen uit)
	2. non is ook voorzien.
Middenzool:	1. Kevlar middenzool om perforatiebestendig te zijn 1100 Newton. (ASTM F2413-05 M I / 75 C / 75, CE ENISO 20345 STANDAARD, een verscheidenheid aan montage om uit te kiezen)
	2. non is ook voorzien
Functie:	Slip / olie / impact / punctie / slijtvast, antistatisch en waterdicht, schokabsorptie, metaalvrij
Stijl:	geen veterlaarzen
Voering:	Air & droog mesh stof of anderen
Inlegzool:	Gegoten HI-POLY of anderen
Bouw:	PU injectie
Hoogte:	30 cm (gemiddeld)
Grootte:	38-46 (4-12)
Garantie:	6 maanden
Pakket:	Kleur binnendoos verpakking, 10 paar in een doos
Grootte van het karton:	68 x 65 x 34,5 cm
Laad hoeveelheid container:	1800 paar / 1x20 'container 3600 paar / 1x40 'container

Product Pictures







Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY