Product Description

Productnaam:	metaalvrije composiet teen antistatische waterdichte laslaarzen voor lassers
Item nr:	W1018
Boven- en zool:	Split gek paardenleer en TPU-bovenwerk, PU- en rubberen zool
Teenkap:	1. Composiet neus om schokbestendig te zijn 200 joule. (ASTM F2413-05 M I / 75 C / 75, CE ENISO 20345 STANDARD, een verscheidenheid aan **passend** kiezen uit)
	2. non is ook voorzien.
Middenzool:	1. Kevlar middenzool om perforatiebestendig te zijn 1100 Newton. (ASTM F2413-05 M I / 75 C / 75, CE ENISO 20345 STANDAARD, een verscheidenheid aan montage om uit te kiezen)
	2. non is ook voorzien
Functie:	Slip / olie / impact / punctie / slijtvast, antistatisch en waterdicht, schokabsorptie, metaalvrij
Stijl:	geen veterlaarzen
Voering:	Air & droog mesh stof of anderen
Inlegzool:	Gegoten HI-POLY of anderen
Bouw:	PU injectie
Hoogte:	30 cm (gemiddeld)
Grootte:	38-46 (4-12)
Garantie:	6 maanden
Pakket:	Kleur binnendoos verpakking, 10 paar in een doos
Grootte van het karton:	68 x 65 x 34,5 cm
Laad hoeveelheid container:	1800 paar / 1x20 'container 3600 paar / 1x40 'container

Product Pictures

RUBBER

Production Process

Raw Materials

Punching

Cutting

Sewing

Eyeletting

Riveting

Heat - Setting

Molding

Making up

Inspection

Packing

Finished Goods

SAFETY SHOES TEST

Toecap Test≥200 Joules

Midsole Test≥1200 Newtons

ESD Anti-Static Test

Tear Strength ≥120N

Bondness Test
≥4.0N/mm

Flex Tester ≥ 36,000T

Canton Fair

SAFETY SHOES

RAIN BOOTS

PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY