

Product Description

| | |
|-----------------------------|--|
| Product Name: | Oil slip resistant composite toe puncture proof anti static sport safety shoes |
| Item No: | BTA044 |
| Upper and Sole: | Genuine cow suede leather PU/ PU dual density creativity sole |
| Toe cap: | Composite toe to be impact resistant 200 joules. (ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 standard) Non is also provided. |
| Mid sole: | Non-metallic anti-penetration mid sole to be puncture resistant 1100 newton. (ASTM F2413-18 M I/75 C/75, CE EN ISO 20345 standard) Non is also provided. |
| | |
| Lace: | Durable round shoes lace |
| Collar: | High density oxford fabric |
| Tongue: | High density mesh fabric |
| Lining: | Breathable air mesh fabric |
| Sockliner: | Moulded EVA or HI-POLY or PU |
| Construction: | PU injection |
| Height: | Low ankle |
| Size: | EUR 37-47 |
| Guarantee: | 6 months |
| Function: | Metal free, slip/ oil/ impact/ puncture resistant, anti static, shock absorption |
| Package: | 1 pair per color box, 10 pairs per carton. Carton size is 58.5 x 40 x 32.5 cm |
| Load quantity of Container: | 3300pairs /1x20' container 6600pairs /1x40' container |

Product Pictures







TIGER MASTER[®] SAFETY SHOES

<https://safetyshoesfactory.com>



COMPOSITE
TOE CAP



NON-METALLIC ANTI
PENETRATION MID SOLE



ANTI-STATIC
SHOE



METAL
FREE



SLIP RESISTANT
SOLE



HEEL ENERGY
ABSORPTION

CE



YOUR SAFETY IS OUR CONCERN!

Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY