

Product Description

Product Name:	China leather steel toe construction site safety shoes S1P
Item No:	DTA032
Upper and Sole:	Upper: Smooth cow split leather Sole: PU dual density
Toe:	1. Steel toe cap, it can be impact resistant 200 Joules. 2. non is also provided.
Midsole :	1. Steel plate, it can be puncture resistant 1100 newton. 2. Non is also provided
Weight:	1.2 kgs/pr
Collar:	High density oxford fabric with sponge
Tongue:	High density oxford fabric
Lining:	Black air & dry sandwich mesh fabric (Your feet will be kept dry and comfortable)
Sockliner:	Moulded EVA or HI-POLY or PU (Greatly reduce your pain & fatigue from daily work)
Construction:	PU Injection
Height:	Low ankle
Size:	37-47 (3-13)
Standard:	CE EN ISO 20345 S1P SRC or others as your requirements
Guarantee:	6 months
Package:	1 pair per color inner box packing, 10 pairs per carton.
Carton Size	58.5 x 40 x 32.5 cm
Load quantity of Container:	3300pairs /1x20' container 6600pairs /1x40' container

Product Pictures





Company Information

Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

SAFETY SHOES TEST



Toecap Test ≥ 200 Joules



Midsole Test ≥ 1200 Newtons



ESD Anti-Static Test



Tear Strength ≥ 120 N



**Bondness Test
 ≥ 4.0 N/mm**



Flex Tester $\geq 36,000$ T

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY