

Product Description

Product Name:	PU injection leather anti static steel toe breathable summer sandals shoes safety
Item No:	DTA035
Upper and Sole:	Upper: Black embossed cow split leather Sole: PU dual density (deltaplus)
Toe:	1. Steel toe cap, it can be impact resistant 200 Joules. 2. non is also provided.
Midsole :	1. Steel plate, it can be puncture resistant 1100 newton. 2. Non is also provided
Weight:	1.1 kgs/pr
Collar & Tongue:	Embossed cow split leather
Style:	No lace summer safety shoes
Lining:	Grey air & dry mesh fabric (Your feet will be kept dry and comfortable)
Sockliner:	Moulded EVA or HI-POLY or PU (Greatly reduce your pain & fatigue from daily work)
Construction:	PU Injection
Height:	Low ankle
Size:	37-47 (3-13)
Standard:	CE EN ISO 20345 S1P SRC or others as your requirements
Guarantee:	6 months
Package:	1 pair per color inner box packing, 10 pairs per carton.
Carton Size	58.5 x 40 x 32.5 cm
Load quantity of Container:	3300pairs /1x20' container 6600pairs /1x40' container

Product Pictures





Company Information



Intertek

EC Type Examination Certificate

	Issued to: FUJIAN HONGJIAN SHISE CO., LTD. SHANGHAI INDUSTRIAL ZONE, JIANGNAN TOWN, NINGBO CITY, ZHEJIANG PROVINCE, CHINA		
Authorised Representative:	Intertek Asia SAFETY PRODUCTS APC (S) LTD 1401 Village Square Street, Jersey Science Centre, Hongkong Science Centre, Hong Kong		
Date of Issue:	11 January 2018		
Expiry Date:	11 February 2020		
Certificate No.:	LEC170002947 (Extension of certificate LEC170294194)		
Product Reference(s):	Safety Group: 48001-48002 48003-48004 48005-48006 48007-48008 48009-48010 48011-48012		
Description:	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;"> Components: Timing: Material: Part: Size: Mount: Test frequency: Test range: Category: </td> <td style="width: 50%; border: none;"> Function: Operate mode: Operate state: Mode: AC/DC: One-wire/Two-wire: I/O: I/O mode: </td> </tr> </table>	Components: Timing: Material: Part: Size: Mount: Test frequency: Test range: Category:	Function: Operate mode: Operate state: Mode: AC/DC: One-wire/Two-wire: I/O: I/O mode:
Components: Timing: Material: Part: Size: Mount: Test frequency: Test range: Category:	Function: Operate mode: Operate state: Mode: AC/DC: One-wire/Two-wire: I/O: I/O mode:		
<div style="display: flex; justify-content: space-between;"> <div style="border: 1px solid black; padding: 2px;"> </div> <div style="text-align: center;"> Product Manager Intertek (Singapore) 110, North Canal Road, #12-01, Singapore 070902 </div> <div style="border: 1px solid black; padding: 2px;"> 1687-02947 Date </div> </div>			

Product Manager
 Intertek (Singapore)
 110, North Canal Road, #12-01, Singapore 070902

1687-02947
 Date

Production Process



Raw Materials



Punching



Cutting



Riveting



Eyeletting



Sewing



Heat - Setting



Molding



Making up



Finished Goods



Packing



Inspection

Canton Fair



SAFETY SHOES



RAIN BOOTS



PROFESSIONAL SAFETY SHOE & RAIN BOOT FACTORY